

**DISCHARGE** 

23/4"-

**Inch** 

21/2"

<u>(mm)</u>

(65)

Inch

<u>(mm)</u>

(100)

Inch

26"

# V.M. 1554-4" Portable Eductor

#### **GENERAL CHARACTERISTICS**

Suction Capacity: 175 – 350 GPM
Suction Lift: Up to 20 Feet
Discharge Head: Up to 80 Feet
Inlet Pressure: 50 – 150 PSI

Weight: 60 Lbs

#### **MATERIALS OF CONSTRUCTION**

Body & Diffuser: Bronze or Aluminum\*\*

\*\*hard coat anodized & powder coated

Nozzle: Monel

### **CONNECTIONS:**

INLET 21/2" IPT

Inlet 2½" NPT Female
Suction 4" NPT Female
Discharge 4" NPT Female

## **Suggested Uses – Marine Departments**

- 1. Keeping bottoms dry during tank or hold washing operations
- 2. Pumping water out of holds during firefighting operations.
- 3. Regular or emergency pumping of liquids from ballast, bilge, cargo spaces, pits, etc.

This model is generally used as a portable eductor and has the ability to fit through small openings but still handles large volumes of liquids. This type also lends itself to permanent installations in tight spaces.

Note:

When suction lift does not exceed 20' a length of suction hose can be attached to the suction end and only the hose is put into the space or liquid to be pumped

#### **OPTIONAL / SPARE ITEMS**

(mm)

(70)

1. Eductor available in bronze & aluminum

Inch

13.12

(mm)

(333)

<u>Inch</u>

16.87

(mm)

(429)

<u>Inch</u>

6.12

(mm)

(155)

2. Optional Lay Flat suction strainer

100.00	
ALC:	
	DEAN.
WE A	
	4 1

<ul><li>3. Optional Barrel Suction Strainer</li><li>4. Swivel NST Adapter fittings</li></ul>											
Suction Capacity		ty	Motive Pressure Motiv		ve flow	e flow Suction Lift		Discharge Head			
<u>GPM</u>	<u>(M3/H</u>	<u>r)</u>	<u>PSI</u>	<u>(BAR)</u>	<u>GPM</u>	<u>(M3/Hr)</u>	FEET	(Meters)	<u>FEET</u>	(meters)	
175-350	(40 - 8	0)	50-150	(3-10)	140-220	(32-50)	0-20	(0-6)	20-60	(6-18)	
INLE	T	Suct	tion & Disc	<u>h</u> <u>A</u>		<u>B</u>	<u>C</u>	<u>D</u>	<u>)</u>	<u>E</u>	

(mm)

(660)

**Inch** 

23/4"

